

IN THE CLAIMS:

Please amend the claims as follows:

1. (Currently Amended): A method of fabricating liquid crystal display (LCD) panels, comprising:

forming a plurality of upper ~~liquid-crystal-display~~ LCD panel sections ~~units~~ having at least two different sizes on a first mother substrate and a plurality of lower ~~liquid-crystal-display~~ LCD panel sections ~~units~~ having at least two different sizes on a second mother substrate;

forming sealant patterns on at least one of the mother substrates;

attaching the first and second mother substrates to each other to bond the upper ~~liquid-crystal-display~~ LCD panel sections ~~units~~ with associated ones of the lower ~~liquid-crystal-display~~ LCD panel sections ~~units~~ to form at least first and second ~~liquid-crystal-display~~ LCD panel units;

forming at least first cutting lines on each of the first and second mother substrates, the first cutting lines corresponding to a boundary of the first ~~liquid-crystal-display~~ LCD panel unit, wherein the first cutting lines extend over at least one sealant pattern;

forming at least second cutting lines on each of the first and second mother substrates, the second cutting lines corresponding to a boundary of the second ~~liquid-crystal-display~~ LCD panel unit; and

separating the first and second ~~liquid-crystal-display~~ LCD panel units into individual ~~liquid-crystal-display~~ LCD panels, wherein the first ~~liquid-crystal-display~~ LCD panel unit is larger than the second ~~crystal-display~~ LCD panel unit,

wherein the first and second mother substrates include a plurality of dummy sections, ~~glass-substrates~~ each dummy section including a main dummy portion ~~glass-substrates~~ and a secondary dummy portion, ~~glass-substrates~~ and at least one of the sealant patterns under the first cutting lines binds the main dummy portions ~~glass-substrates~~ and secondary dummy portions ~~glass-substrates~~ together during the separating step.

2. (Canceled).

3. (Currently Amended): The method according to claim 1, wherein the secondary dummy portions ~~glass-substrates~~ have a width of less than about 3 mm.

4. (Currently Amended): The method according to claim 1, wherein the sealant patterns are formed on non-display regions of the ~~liquid-crystal-display~~ LCD panels.

5. (Currently Amended): The method according to claim 1, wherein the sealant patterns are positioned on both the main dummy portions ~~glass-substrates~~ and the secondary dummy portions ~~glass-substrates~~.

6. (Currently Amended): The method according to claim 1, wherein sizes of the upper ~~liquid-crystal-display~~ LCD panel sections ~~units~~ on the first mother substrate and the lower ~~liquid-crystal~~

~~display LCD panel sections units~~ on the second mother substrate facing correspondingly at each other are substantially the same.

7. (Currently Amended): The method according to claim 1, wherein the lower ~~liquid crystal display LCD panel sections units~~ have a plurality of thin film transistors and a plurality of pixel electrodes, and the upper ~~liquid crystal display LCD panel sections units~~ have a plurality of color filters and a common electrode.

8. (Currently Amended): A method of fabricating liquid crystal display (LCD) panels, comprising:

forming a plurality of upper ~~liquid crystal LCD panel sections units~~ having at least two different sizes on a first mother substrate and a plurality of lower ~~liquid crystal display LCD panel sections units~~ having at least two different sizes on a second mother substrate;

forming sealant patterns on at least one of the mother substrates;

attaching the first and second mother substrates to each other to bond the upper liquid crystal display LCD panel sections units with associated ones of the lower ~~liquid crystal display LCD panel sections units~~ to form at least first and second ~~liquid crystal display LCD panel units~~;

forming at least first and second cutting lines on each of the first and second mother substrates; and

separating the first and second ~~liquid-crystal display~~ LCD panel units into individual ~~liquid-crystal display panel units~~ LCD panels having different sizes,

wherein remnants of the separated mother substrates include main dummy portions ~~glass substrates~~ and secondary dummy portions ~~glass substrates~~ divided by the first cutting lines therebetween, and at least one of the sealant patterns is located underneath the first cutting lines ~~between the main dummy glass substrates and the secondary dummy glass substrates, wherein~~ such that at least one of the sealant patterns under the first cutting lines bind the main dummy portions ~~glass substrates~~ and secondary dummy portions ~~glass substrates~~ together during the separating step.

9. (Currently Amended): The method according to claim 8, further comprising injecting liquid crystals into the separated LCD panels ~~liquid-crystal display panel units~~.

10. (Currently Amended): The method according to claim 8, wherein the secondary dummy portions ~~glass substrates~~ have a width of less than about 3 mm.

11. (Currently Amended): The method according to claim 8, wherein sizes of the upper ~~liquid-crystal display~~ LCD panel sections ~~units~~ on the first mother substrate and the lower ~~liquid-crystal display~~ LCD panel sections ~~units~~ on the second mother substrate facing correspondingly at each other are substantially the same.

12. (Currently Amended): The method according to claim 8, wherein the lower ~~liquid-crystal display LCD~~ panel sections ~~units~~ have a plurality of thin film transistors and a plurality of pixel electrodes, and the upper ~~liquid-crystal display LCD~~ panel sections have a plurality of color filters and a common electrode.

13. (Currently Amended): The method according to claim 1, further comprising injecting liquid crystals into the separated LCD panels ~~liquid-crystal display panel units~~.

14. (Canceled).

15. (Canceled).

16. (Currently Amended): A method of fabricating liquid crystal display (LCD) panels, comprising:

forming a plurality of upper ~~liquid-crystal display LCD~~ panel sections ~~units~~ on a first substrate and a plurality of lower ~~liquid-crystal display LCD~~ panel sections ~~units~~ on a second substrate;

forming sealant patterns extending in a first direction on at least one of the substrates;

attaching the first and second substrates to each other to bond the upper ~~liquid-crystal display LCD~~ panel sections ~~units~~ with associated ones of the lower ~~liquid-crystal display LCD~~ panel sections ~~units~~ to form at least first and second ~~liquid-crystal display LCD~~ panel units;

forming a first set of cutting lines substantially in the first direction on each of the first and second substrates, the first set of cutting lines spanning the entire width of the first and second substrates and corresponding to a boundary of the first ~~liquid-crystal display LCD~~ panel unit, wherein the first set of cutting lines extend directly over at least one sealant pattern;

forming a second set of cutting lines substantially in the first direction on each of the first and second mother substrates, the second set of cutting lines spanning only a portion of the first and second substrates and corresponding to a boundary of the second ~~liquid-crystal display LCD~~ panel; and

separating the first and second ~~liquid-crystal display LCD~~ panel units into individual ~~liquid-crystal display LCD~~ panels,

wherein remnants of the first and second substrates include at least one main dummy portion glass-substrate and at least one secondary dummy portion glass-substrate divided by the first set of cutting lines therebetween, and at least one of the sealant patterns under the first set of cutting lines binds the main dummy portion glass-substrate and secondary dummy portion glass substrate together during the separating step.

17. (Currently Amended): The method according to claim 16, wherein the first ~~liquid-crystal display~~ LCD panel unit is larger than the second ~~crystal-display~~ LCD panel unit, the main dummy portion ~~glass-substrate~~ and the secondary dummy portion ~~glass-substrate~~ being formed between a plurality of second ~~crystal-display~~ LCD panel units.